

KFH- Karver Furling Hook (Lock)

The KFH external lock is a lock for headsails, easy to install. It makes it possible to no longer have tension in the halyard and, avoid wears and stretch for more safety, less weight, and more performance The KFH includes a lock + a swivel which means you can use it to furl any kind of front sails. Ultra compact, ultra light, ultra reliable.

- Compact & Light
- Easy to install on new builds & retrofits. Easy to service.
- Essential product for racing and Super Yacht, but also suited for any cruising yachts
- No trip line: the halyard is used to lock and unlock the system
- The rounded edge of the parts secures the engagement of the male part into the female part to lock
- Electronic position sensor, available as an upgrade



Part #	Models	Material *	Spring	Safe Working Load (T)	Breaking Load (T)	Weight (kg)	Height (mm)	Fast pin (mm)	Fork width (mm)	Halyard ending	Halyard hole (mm)	Max halyard (mm)
PF550020 [KFH]	KFH1	Alu / SS	Outside	1,5	3	0,180	100	8	11	Sewn knot	5	5
PF480020 [KFH]	KFH2	Alu / SS	Outside	2,5	5	0,450	141	10	18	Sewn knot	8	8
PF470020	KFH5	Alu / SS	Inside	5	10	0,920	154	12	20	T Bone	9,5	6
PF410020 [KFH6]	KFH6	SS / Titanium	Inside	6	12	0,900	155	14	24	T Bone	9,5	6
PF410020	KFH8	SS / Titanium	Inside	8	16	1,040	155	14	24	T Bone	9,5	6
PF390020	KFH10	SS / Titanium	Inside	10	20	2,100	205	18	22	T Bone	11	8
PF400020 [14]	KFH14	SS / Titanium	Inside	14	28	2,200	212	20	22	T Bone	11	8
PF440020	KFH20	SS / Titanium	Inside	20	40	4,100	277	25	32,5	T Bone	14	10

* Alu = Aluminum / SS = Stainless steel

*We can manufacture KFH featuring higher working load or custom to your application, upon demand.
The KFH is designed to accommodate the smallest halyard diameter, but can be customized for bigger ones.*